

Thor's 13 Hammers

Master-Level Thermal Imaging



1022°F

Pro High Temp
±1.5°C Accuracy



512×384

Super
IR-Resolution



8cm

Macro Lens



4x

Digital
Zoom



3.5"

640×480
IPS Display



9-Point

Temp
Measurement

Specifications

Model		THOR001	THOR002
Key Features	Temperature Range	-20~550°C	
	Accuracy	±1.5°C or ±1.5% of the reading	±2°C or ±2% of the reading
	IR Resolution	256×192	
	Super IR Resolution	512×384	
	Macro Lens	√	×
	Lens Focal Length	4.3mm	
	Digital Zoom	2/4×	
	Display	3.5 inch IPS (640×480)	
	Spot Meter	Center spot/Max/Min/6 Custom Spots/Temperature difference	Center spot/Max/Min/3 Custom Spots/Temperature difference
	NETD/Thermal Sensitivity	< 35mk	< 40mk
	Image Mode	Fusion, IR (default), PIP, Visual	
	Digital Camera	2MP	
	Wireless	√	
	PC-based Analysis Software	Supports 13 languages (English by default)	
	APP	√	
	Laser Indicator	√	
	Microphone	√	
	Flash Shield	Lens cap for protection	
	Alloy Metal Base	√	
Imaging & Optical	IQ+	√	
	Razor X	√	
	AI{Det}	√	
	Color Palettes	White hot, Black hot, Lava,Iron (default), Rainbow,Rainbow HC, Black red,High temperature highlight,Low temperature highlight	White hot, Black hot, Lava,Iron (default), Rainbow, Rainbow HC, Black red
	Image Frequency	25Hz	
	FOV	40°×30°	
	IFOV	2.79mrad	
	Pixel Pitch	12μm	
	Focus Mode	Fixed focus	
	Min Focus Distance	8cm	30cm
Measurement & Analysis	Screen Refresh Rate	60Hz	
	Image Capture	Manual,Time-lapse image capture	
	Video Recording	Support (MP4,OSD info)	
	QR Code Scanning	√	
	Measurements Correction	Emissivity,Ambient temperature,Distance compensation	
	Language	Supports 13 languages (English by default)	
	Isotherm	√	
	Temperature Alarm	Max/Min temperature alarm	
	Alarm Method	Image pop-up, flashlight prompt	
	Auto Image Capture on Alarm	√	
Power	Image Saving	Auto, manual	
	Video Transmission	√	
	Fast Charge	18W	
	Battery	5000mAh rechargeable lithium battery	
	Charging Time	4h	
Accessories	Operating Time	8h	
	Auto Shutdown	Configurable(Off,5minutes,10 minutes,20minutes, 120 minutes)	
	Storage	8GB RAM 32GB storage card	
	LED Lamp	Supports lighting and flashlight modes	
	Hard Case	√	
	Tripod Mount	√	
	Protection Level	IP54	
	Tool Belt	√	
	Type-C 2.0	Charging, data transfer	
	Operating Temperature	-20 to +55°C	
	Storage Temperature	-20 to +60°C	
	Relative Humidity	10% to 95%,non-condensing	
	Package Contents	USB cable, SD card, user documentation, certificate of conformity, calibration certificate, macro lens	

About Us

M.V. INDUSTRIAL GROUP
 Tel: 0521 573327
 Web: www.mv-ig.com
 E-mail: mv@mv-ig.com